




BOULY WALL/CEILING



Material	Materiaal	Matériau
aluminium - PMMA	aluminium - PMMA	aluminium - PMMA
Finish	Afwerking	Finition
black - chrome - grey - white PMMA : transparent lens : PMMA	zwart - chroom - grijs - wit PMMA : transparent lens : PMMA	noir - chrome - gris - blanc PMMA : transparent lentille : PMMA
Lightsource	Lichtbron	Source lumineuse
4 x power LED (included) 1.2W cold white : 6000K - 440lm - CRI >75 4 x LED (included) 0.96W warm white : 2700K - 456lm - CRI >93	4 x power LED (inclusief) 1.2W koud wit : 6000K - 440lm - CRI >75 4 x LED (inclusief) 0.96W warm wit : 2700K - 456lm - CRI >93	4 x power LED (inclus) 1.2W blanc froid : 6000K - 440lm - CRI >75 4 x LED (inclus) 0.96W blanc chaud : 2700K - 456lm - CRI >93
Connection	Aansluiting	Connexion
350mA - driver excluded	350mA - voeding exclusief	350mA - convertisseur exclus
Specifications	Specificaties	Spécifications
indoor wall or ceiling mounting class III IP50	binnen wand- of plafondmontage klasse III IP50	intérieur applique ou plafonnier classe III IP50

